

FINEPIX JV500

Look the part for less

The FinePix JV500 is the perfect match for any strangers to photography. With a 14 megapixel resolution sensor, a 3x FUJINON optical zoom lens, a 2.7inch LCD screen and a large collection of easy-to-use features, this compact camera is raring to go! Features such as Scene Recognition Auto, Anti-blur, Smile and Shoot mode and Motion Panorama, are guaranteed to keep beginner photographers on their toes! What's more with 3 exciting colours to choose from, the FinePix JV500 from FUJIFILM, will be sure to look the part!



Key Features

- | | | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> • 14 megapixel CCD sensor • 3x FUJINON optical zoom (38-114mm equivalent) • 2.7inch LCD screen (230K dots) • Anti-blur feature • Face Detection | <ul style="list-style-type: none"> • Smile and Shoot mode • 3-step Motion Panorama • Easy Web Upload to Facebook and YouTube • Scene Recognition Auto • HD video capture (30fps) | <ul style="list-style-type: none"> • Lithium-ion battery operated (approx 200 shots) • Charge via USB cable (cable and plug included) • ISO sensitivity up to 1600* |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

* At reduced resolution

14
MP

3x
FUJINON
ZOOM

2.7"
LCD

HD
MOVIE

f YouTube

Dedicated Accessories

UNIVERSAL ZIPPED CASE



AV-C1 AV CABLE



- | | |
|------------------------------------------|-------------|
| • Universal Zipped Case | P10NA03650A |
| • AC Power Supply AC-5VX | P10N004210A |
| • CP-45 Coupler (requires AC-5VX) | P10NA00180A |
| • Lithium-ion Rechargeable Battery NP-45 | P10NA00200A |
| • Battery Charger BC-45W | P10NA01040A |
| • AV Cable AV-C1 | P10NA00990A |

Included Accessories

- | | |
|-------------------------------------|------------------|
| • Li-ion Rechargeable Battery NP-45 | • Hand Strap |
| • AC Power Adaptor | • CD-ROM |
| • USB Cable | • Owner's Manual |

Universal Accessories

STORAGE MEDIA CARDS



WORLDTRIP DUAL USB CHARGER & TRAVEL ADAPTOR



SD™/SDHC™/SDXC™ MEMORY CARDS (2GB-64GB)

- | | |
|-----------------------------------------------|-------------|
| • SD™/SDHC™/SDXC™ Memory Cards (2GB-64GB) | |
| • Universal Case and 2GB SD Card Pack | P10NA03660A |
| • WorldTrip Dual USB Charger & Travel Adaptor | P10NA00870A |
| • PowerSafe Earthed Travel Adaptor | P10NA00890A |
| • World Adaptor | P10NA04350A |
| • World Adaptor with USB Charger | P10NA04360A |
| • SD™/SDHC™ USB Card Reader | P10NM00930A |
| • Gorillapod (small) | P10NA00290A |
| • 2.7inch Screen Protector | P10NA00430A |
| • Lens Cleaning Kit | P10NA04250A |

Technical Specification			
Number of effective pixels	14 million pixels		
Image sensor	1/2.3inch CCD with primary colour filter		
Storage media	Internal memory (none) SD™/SDHC™/SDXC™ memory card		
File format Still Image	JPEG (Exif Ver 2.3) (Design rule for Camera File system compliant / DPOF-compatible)		
Movie	AVI (Motion JPEG)		
Number of recorded pixels	L: (4:3) 4288 x 3216 (3:2) 4288 x 2864 (16:9) 4288 x 2416 M: (4:3) 3072 x 2304 (16:9) 3072 x 1728 S: (4:3) 2048 x 1536 (16:9) 1920 x 1080		
Lens	FUJINON 3x optical zoom lens		
Focal length	f=6.8-20.4mm, equivalent to 38-114mm on a 35mm camera		
Full-aperture	F3.9 (Wide) – F5.9 (Telephoto)		
Constitution	5 groups 5 lenses		
Digital zoom	Approx. 6.3x (up to approx. 18.9x, with 3x optical zoom)		
Aperture	F3.9 (Wide) F5.9 (Telephoto)		
Focus distance (from lens surface)	Normal: Wide: Approx. 60cm to infinity / 2.0 ft to infinity Telephoto: Approx. 60cm to infinity / 2.0 ft to infinity Macro: Wide: Approx. 10cm – 70cm / 0.3ft – 2.3ft Telephoto: Approx. 60cm – 1.0m / 2.0ft – 3.3ft		
Sensitivity	Auto, Equivalent to ISO 100/200/400/800/1600 (Standard Output Sensitivity)		
Exposure control	TTL 256-zones metering		
Exposure mode	Programmed AE		
Shooting modes	SR AUTO, AUTO, P, Movie, Natural Light & with Flash, Natural Light, Portrait, Smile & Shoot, Landscape, Motion Panorama, Sport, Night, Night (Tripod), Sunset, Snow, Beach, Flower		
Mode dial	–		
Image stabiliser	–		
Anti blur	Yes		
Face detection	Yes		
Exposure compensation	-2.0EV – +2.0EV, 1/3EV step		
Shutter speed	Auto: 1/4 second to 1/2000 second All other modes: 4 seconds to 1/2000 second with mechanical shutter		
Continuous shooting (TOP)	–		
(LAST)	–		
(Others)	–		
Auto bracketing	–		
Focus	Single AF/Continuous AF (SR AUTO)		
(Type)	TTL contrast AF		
(AF frame selection)	Centre		
White balance	Automatic scene recognition Preset: Fine, Shade, Fluorescent light (Daylight), Fluorescent light (Warm White), Fluorescent light (Cool White), Incandescent light		
Self-timer	Approx. 10 seconds / 2 seconds delay		
Flash	Auto flash (i-flash) Effective range: (ISO AUTO) Wide: Approx. 60cm – 4.3m / 1.9ft – 14.1ft Telephoto: Approx. 60cm – 2.8m / 2.0 ft – 9.3ft Macro Wide: Approx. 30cm – 70cm / 0.9ft – 2.3ft Telephoto: Approx. 60cm – 1.0m / 2.0ft – 3.3ft		

FUJIFILM



All images are simulated.

Flash modes	Face detection OFF: Auto, Forced Flash, Suppressed Flash, Slow Synchro. Face detection ON: Red-eye Reduction Auto, Red-eye Reduction and Forced Flash, Suppressed Flash, Red-eye Reduction and Slow Synchro.
Hotshoe	–
Electronic Viewfinder	–
LCD monitor	2.7inch, approx. 230,000 dots, TFT colour LCD monitor, approx. 96% coverage
Movie recording	1280x720 pixels / 640x480 pixels / 320x240 pixels. (30 frames / second) with monaural sound. Zoom function can be used. Sounds will not be recorded during optical zoom operation. During movie playback with the camera, the sound doesn't come out.
Photography functions	SR AUTO, Face Detection, Blink detection, Framing guideline, Automatic LCD brightness adjustment, Frame No. memory, Date stamp
Playback functions	Face Detection, Photobook assist, Image search, Erase selected frames, Slide show, Crop, Resize, Image rotate, Mark for upload, Multi-frame playback, Panorama
Other functions	PictBridge, Exif Print, Print Image Matching II 30 languages selection, Time difference, Silent mode
Terminal (Video output)	NTSC PAL selectable with monaural sound
(Digital interface)	USB 1.1 Full-Speed
(HDMI output)	–
Power supply	NP-45A Li-ion battery or NP-45B Li-ion battery (included)
Dimensions	96.0mm(W) x 59.8mm(H) x 32.0mm(D) 3.7in(W) x 2.4in(H) x 1.3in(D) (Minimum depth: 18.3mm/0.7in)
Weight	Approx. 120g / 4.2oz (including accessories, battery and memory card) Approx. 100g / 3.5oz (excluding accessories, battery and memory card)
Operating temperature	0°C – 40°C
Operating humidity	10% – 80% (no condensation)
Battery life	Approx. 200 frames (AUTO mode)

Number of Images							
	Recording format	Internal memory		4GB		8GB	
Mode		FINE	NORMAL	FINE	NORMAL	FINE	NORMAL
Still images	L 4:3	NO INTERNAL MEMORY		550	1090	1110	2180
	L 3:2			620	1220	1240	2440
	L 16:9			730	1430	1470	2870
	M 4:3			1060	2060	2130	4120
	M 16:9			1400	2690	2810	5380
	S 4:3			2300	4290	4600	8580
	S 16:9			3360	6080	6720	12160
	Movies ¹			HD1280 ²			18 (min.)
640				55 (min.)		111 (min.)	
320				116 (min.)		233 (min.)	

Product Code
P10NC10410A
P10NC10420A
P10NC10450A

Barcode
4547410229370
4547410229400
4547410229394

Colour
Black
Blue
White

- ¹ Individual movie files cannot exceed file size of 2GB (approx. half of 4GB time in above table) or 29 minutes.
² Use a Class 4 card or better when shooting HD movie.